

# ARCHI

## Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

### GENERAL CHARACTERISTICS

Composition	99% Sunbrella Acrylic 1% PES		
Backing / Finish	Water-repellent & Stain-proof		
Weave	Fancy weave		ISO 7211-1
Weight	585	g/m <sup>2</sup>	ISO 3801
Width	140	cm	EN 1773
Roll length	25	ml	



### FABRIC RESISTANCE

Tensile strength	317	116	daN/5cm	ISO 13934-1
Elongation at break	46.7	62	%	ISO 13934-1
Pilling	4		Class / 5	ISO 12945-2
Spray test	5		Class / 5	ISO 4920
Seam slippage (180 N)	<1	<5	mm	ISO 13936-2
Stitching strength	469	559	N	ISO 13935-2
Stability on 30 deg. C washing	±2.5	±1	%	ISO 5077



### COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4/5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 30°C washing	5		Class / 5	ISO 105 C06



### FIRE RESISTANCE

California Technical Bulletin 117-203 Section 1	Pass
NFPA 260 Classe I	Pass
NF EN 1021-1	Pass
BS 5852 Part 1 Source 0	Pass

### USES

Guarantee	5	years
Recommended Uses	Seating, Cushions	

### CARE



This product's values may vary with a tolerance of ± 5%

**Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration**

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com/en/UK](http://www.dickson-constant.com/en/UK)