

SEAMARK

Technical sheet

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella solution dyed acrylic + one side PVC			
Backing / Finish	Special marine treatment			
Weave	Canvas			ISO 7211-1
Weight	542		g/m²	ISO 3801
Width	152		cm	EN 1773

FABRIC RESISTANCE

Tensile strength	100	56	daN/5cm	ISO 13934-1
Tear strength	14.00	6.00	daN	ISO 13937-1
Abrasion	40000		NT	ISO 12947-2
Schmerber	5000		mm	ISO 811
Spray test	5		Class / 5	ISO 4920

USES

Guarantee	5	years	
Recommanded Uses	Sprayhood, Rear enclosure, Bimini top, Cockpit enclosure, Windscreen cover, Dodger, Console cover, Winter cover, seat cover		

COLOUR-FASTNESS

Colorfastness to Light	Grade 4 @ 220 Kj		AATCC 169-2003 Option 3
Colorfastness to Light (SAE)	Grade 4/5 @ 1500 Kj		SAE 1960J

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration
10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK