

# SLOW

## Technical sheet



| CHARACTERISTICS | VALUES |      | UNITS | STANDARDS |
|-----------------|--------|------|-------|-----------|
|                 | WARP   | WEFT |       |           |

### GENERAL CHARACTERISTICS

|                  |                                                                   |  |      |            |
|------------------|-------------------------------------------------------------------|--|------|------------|
| Composition      | 33% Recycled Sunbrella Acrylic 65% Sunbrella Acrylic 2% Polyester |  |      |            |
| Backing / Finish | Non PFAS - Water-repellent & Stain-proof                          |  |      |            |
| Weave            | Jacquard                                                          |  |      | ISO 7211-1 |
| Weight           | 470                                                               |  | g/m² | ISO 3801   |
| Width            | 140                                                               |  | cm   | EN 1773    |
| Roll length      | 35                                                                |  | ml   |            |

### FABRIC RESISTANCE

|                                |       |      |           |             |
|--------------------------------|-------|------|-----------|-------------|
| Tensile strength               | 124   | 90   | daN/5cm   | ISO 13934-1 |
| Elongation at break            | 18    | 30   | %         | ISO 13934-1 |
| Pilling                        | 5     |      | Class / 5 | ISO 12945-2 |
| Spray test                     | 5     |      | Class / 5 | ISO 4920    |
| Seam slippage (180 N)          | < 0.3 | < 1  | mm        | ISO 13936-2 |
| Stitching strength             | 550   | 570  | N         | ISO 13935-2 |
| Stability on 30 deg. C washing | -1.8  | -0.5 | %         | ISO 5077    |

### COLOUR-FASTNESS

|                                      |     |  |           |             |
|--------------------------------------|-----|--|-----------|-------------|
| Colour fastness UV - outdoor - 1000h | 4-5 |  | Class / 5 | ISO 105 B04 |
| Colour fastness UV - indoor          | 8   |  | Class / 8 | ISO 105 B02 |
| Colour fastness under dry friction   | 5   |  | Class / 5 | ISO 105X12  |
| Colour fastness under wet friction   | 5   |  | Class / 5 | ISO 105X12  |
| Colour fastness 30°C washing         | 5   |  | Class / 5 | ISO 105 C06 |

### FIRE RESISTANCE

|                                                 |      |
|-------------------------------------------------|------|
| California Technical Bulletin 117-203 Section 1 | PASS |
| NFPA 260 Classe I                               | PASS |
| NF EN 1021-1                                    | PASS |
| BS 5852 Part 1 Source 0                         | PASS |

### USES

|                  |                   |       |
|------------------|-------------------|-------|
| Guarantee        | 5                 | years |
| Recommended Uses | Seating, Cushions |       |

### CARE



This product's values may vary with a tolerance of  $\pm 5\%$

**Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration**

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com/en/UK](http://www.dickson-constant.com/en/UK)



**STANDARD 100**

CQ 638/10  
IFTH

