

VELUM XL

Technical sheet

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella Acrylic		
Backing / Finish	Non PFAS - Water-repellent & Stain-proof		
Weave	Velum		ISO 7211-1
Weight	170	g/m ²	ISO 3801
Width	300	cm	EN 1773
Roll length	40	ml	

FABRIC RESISTANCE

Tensile strength	84	55	daN/5cm	ISO 13934-1
Elongation at break	22	23	%	ISO 13934-1
Spray test	4		Class / 5	ISO 4920
Stability on 30 deg. C washing	±1.5	±1.5	%	ISO 5077
Steam stability	1.50	1.50	%	

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5	Class / 5	ISO 105 B04
Colour fastness UV - indoor	8	Class / 8	ISO 105 B02
Colour fastness under dry friction	5	Class / 5	ISO 105X12
Colour fastness under wet friction	5	Class / 5	ISO 105X12
Colour fastness 30°C washing	5	Class / 5	ISO 105 C06

USES

Guarantee	5	years	
Recommended Uses	curtains, pergolas, roman blinds		

CARE



This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK